

Elcometer 3238 Long Edge Wet Film Combs (Stainless Steel)

These stainless steel combs are wire eroded to provide an accuracy of $\pm 2.5\mu\text{m}$ (0.01mil) and are supplied with either Metric or Imperial measurements.

Each comb has 24 measurement steps (teeth) providing a more accurate wet film thickness value.



STANDARDS:

ASTM D 4414-A, AS/NZS 1580.107.3, BS 3900-C5-7B, ISO 2808-1A, ISO 2808-7B, JIS K 5600-1-7, NF T30-125, US Navy PPI 63101-000, US Navy NSI 009-32

Technical Specification

| Metric Combs | | | | Imperial Combs | | | |
|--------------|---|-------------------|-------------|----------------|--------------|-------------------|-------------|
| Part Number | Range | Measurement Steps | Certificate | Part Number | Range | Measurement Steps | Certificate |
| K0003238M201 | 5 – 120 μm | 5 μm | ○ | K0US3238M201 | 0.5 – 6mils | 0.5mil | ○ |
| K0003238M202 | 25 – 600 μm | 25 μm | ○ | K0US3238M202 | 1.0 – 24mils | 1.0mil | ○ |
| K0003238M203 | 50 – 1200 μm | 50 μm | ○ | K0US3238M203 | 2.0 – 48mils | 2.0mil | ○ |
| K0003238M204 | - | Set of 3 Combs | ○ | K0US3238M204 | - | Set of 3 Combs | ○ |
| Accuracy | $\pm 5\%$ of marked value or 3 μm (0.12mil) whichever is the greater | | | | | | |

○ Optional Calibration Certificate available.