elcometer®
inspection equipment

Elcometer Protective Coating Inspection Kit 4

The Elcometer Protective Coatings Inspection Kit 4 provides a range of test equipment to help an inspector assess a substrate prior to the application of a coating.

Measurement parameters include:

* Surface inspection
* Weld inspection
* Surface cleanliness
* Climatic conditions
* Surface profile
* Coating thickness

compatible with
ElcoMaster®

available with
Bluetooth®
wireless technology

STANDARDS:

AS 2331.1.4, AS 3894.3-B, AS 3894.6-A, AS 3894.6-C, AS 3894.9, AS/NZS 1580.107.3, AS/NZS 1580.108.1, ASTM B 499, ASTM D 1186-B, ASTM D 1400, ASTM D 2200, ASTM D 4414-A, ASTM D 4417-C, ASTM D 7091, ASTM E 376, ASTM G 12, BS 3900-C5-6A, BS 3900-C5-6B, BS 5411-11, BS 5411-3, BS 5599, BS 7079-B4, BS 7079-C5, DIN 50981, DIN 50984, ECCA T1, EN 13523-1, IMO MSC.215(82), IMO MSC.244(83), ISO 1461, ISO 19840, ISO 2063, ISO 2360, ISO 2808-12, ISO 2808-1A, ISO 2808-6A, ISO 2808-6B, ISO 2808-7B, ISO 2808-7C, ISO 2808-7D, ISO 8501-1, ISO 8502-3, ISO 8502-4, ISO 8502-6, ISO 8502-9, ISO 8503-5, JIS K 5600-1-7, NACE RP0287, NF T30-124, NF T30-125, SANS 5772, SS 184159, SS 55900, SSPC Guide 15, SSPC PA 2, SSPC VIS 1, SSPC VIS 2, SSPC VIS 3, SSPC VIS 4, SSPC VIS 5, US Navy NSI 009-32, US Navy PPI 63101-000

Contents

Model	Description
Elcometer 128	Pictorial Standards[1]
Elcometer 131/1C	Telescopic Inspection Mirror
Elcometer 144	Paint Safe Marker Pens (Pack of 3)
Elcometer 147	Weld Gauge
Elcometer 142	Dust Tape Test Kit
Elcometer 138	Bresle Salt Kit[2]
Elcometer 319	Digital Dewpoint Meter with Magnetic Surface Probe Top
Elcometer 224	Integral Digital Surface Profile Integral Gauge Model T
Elcometer 112	Hexagonal Wet Film Comb: 25 - 3000µm (1 - 120mils)
Elcometer 456	Separate Digital Coating Thickness Gauge with F2 Standard Probe, Ferrous Model T
ElcoMaster®	Data Management Software & USB Cable

Technical Specification

Part Number Metric	Imperial	Description
YKIT-PROTECTIVE-4M	YKIT-PROTECTIVE-4E	Elcometer Protective Coatings Kit 4
Dimensions		495 x 420 x 175mm (19.49 x 16.54 x 6.89")

[1] Swedish Rust Standard ISO 8501, SIS055900 supplied in Metric Kit, US Standard SSPC VIS 1-01 and VIS-3 supplied in Imperial Kit
[2] Supplied with Elcometer 135C Bresle Test Patches (x50)